

SPECIFICATIONS

December 2020

CB Film (formerly BB1119)

APPLICATIONS: General purpose converted bags
Wicket bags
Side weld bags

DESCRIPTION: High gloss & very good clarity
Enhanced stiffness
Easy hot knife or wire cut

SPECIFICATIONS:

Property	Units		1.25 mil	2.5 mil
Tensile Break	PSI	MD	4512	4162
	PSI	TD	3869	4142
Tensile Elong.	%	MD	466	604
	%	TD	734	803
Tear	grams	MD	43	235
	grams	TD	426	924
Spencer Impact	grams	N/A	559	612
Yield	sq.in./lb.	N/A	24,000	12,000

AVAILABILITY: Single wound sheeting 10" – 60" wide Thickness range 0.00125" – 0.008"
Center-fold sheeting 10" – 60" wide Thickness range 0.002" – 0.008"
Color Natural or tinted blue

**General
Films, Inc.**
INNOVATIONS IN PACKAGING

645 South High Street
Covington, Ohio 45318
P: 937.473.2051
F: 937.473.2403
W: www.generalfilms.com

The information contained herein is based upon data believed to be reliable and relates only to the matters specifically contained herein. Although such information is, to the best of our knowledge and belief, accurate and reliable as of the date hereof, no representation, warranty (express or implied, or merchantability, fitness or otherwise), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information. It is the user's responsibility to satisfy itself as to the suitability, accuracy, reliability and completeness of such information for its particular use. There is no warranty against patent infringement and General Films will not be liable for any loss, damage, or injury that may occur from the use of this information. No statement herein shall be construed as an endorsement of any product or process.