Specifications

March 2011

DURATUF 75

APPLICATIONS: Industrial packaging

General purpose polyethylene

Non critical uses

Temperature use to 180 F

DESCRIPTION: Single layer film

Two sided sealing Wide spec LLDPE

Low cost

SPECIFICATIONS:

Property	Units		1.5 mil	2.5 mil	3.5 mil	4.5 mil
Dart	grams		65	140	200	320
Secant	Psia	MD	25000	26000	27000	28000
modulus	Psia	TD	33000	31000	32000	32000
Tensile	Psia	MD	3000	3000	3000	3000
(at break)	%		600	600	600	600
	Psia	TD	2500	2500	2500	2500
	%		600	600	600	600
Tear	grams	MD	50	160	340	580
	grams	TD	350	620	780	990

Availability:Bottom seal bags 9" - 110" wide, 20" - 275" deep

Side seal bags 20" - 275" wide, 10" - 110" deep

Tubing 9" - 120" wide.
Single wound sheeting 10" - 120" wide.
Center fold sheeting 10" - 120" wide.
Thickness range 1.25 to 6.0 mils
Color natural, black



INNOVATIONS IN PACKAGING

645 SOUTH HIGH STREET COVINGTON, OHIO 45318 P: 937.473.2051 F: 937.473.2403

W: WWW.GENERALFILMS.COM